



Technical features:

- Steel case
- Steel faceplate
- Lamellar steel deadbolt protected by single throw armour plating
- 13 mm driving gears stroke for additional locking points
- Spindle for operating the dead bolt and driving gears
- Deadbolt resistance equivalent to Grade 3 Security of the European Standard EN 12209:03
 - Side load resistance: 1,000 kg (equivalent to highest grade according to the above Standard)
 - Resistance to blows from below: 400 kg
- Suitable for doors certified to EN 1627:2011 up to WK/RC 2 resistance class

Supplied as standard:

- Cylinder fixing screws

Finishes:

- Zinc-plated case
- Zinc-plated faceplate
- Zinc-plated deadbolt

Hand:


0 = Non-handed

Cylinder to be ordered separately




0G303, 0G305,
0E303, 0E305

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM			
								Type	Dim.	Hand	Fin.



- Latch bolt only
- CAN BE USED WITH THE FOLLOWING ACCESSORIES:
European profile cylinders with special cam:
Item 1-0G305-02-0-12 (C2000 single cylinder)
Item 1-0G303-07-0-12 (C2000 double cylinder)
Item 1-0E305-02-0-12 (ASIX single cylinder)
Item 1-0E303-07-0-12 (ASIX double cylinder)
Handle art. 1-06003-00-0
Handle with edge cover art. 1-06004-00-0
Striking plate art. 1-06232-21-0
Adjustable striking plate art. 1-06232-22-0
Screwed extended bolts art. 1-07088-03-0

1	59	25	19,7	0,590	24	1	46305	19	0		
1	59	25	25,7	0,672	24	1	46305	25	0		
1	59	25	31	0,780	24	1	46305	30	0		



- Dead bolt only
- Pin key cylinder complete with 2 pieces item 1.00210.00.0 (KA 1 version, key included)
- CAN BE USED WITH THE FOLLOWING ACCESSORIES:
Handle item 1.06003.01.0
Handle with edge cover item 1.06004.01.0
Striker item 1.06232.21.0
Adjustable striker item 1.06232.22-0
Extended bolts item 1.07088.03.0

1	59	25	19,7	0,709	24	1	46307	19	0		
1	59	25	25,7	0,804	24	1	46307	25	0		