



Technical features:

- Zinc plated steel case
- Satin brass faceplate and striking plate
- Reversible, electric latch
- 12 V ac CE
- Rated current 2,8 A

Supplied as standard:

- Electric contacts 1.06510.00.0
- Striking plate
- Lock and cylinder fixing screws
- Instruction sheet

On request:

- Satin nickel-plated brass (fin. 12)


Hand:

0 = Non-handed

Cylinder to be ordered separately



Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
								Type	Dim.	Hand	Fin.



- Manual latch and dead-bolt
- SUPPLIED AS STANDARD:
Striking plate item 1.06035.00.0 (L=25 mm.)

2	22	40	0,997	1	1	12010	40	0			
2	22	50	1,040	1	1	12010	50	0			
2	22	60	1,130	1	1	12010	60	0			
2	22	70	1,138	1	1	12010	70	0			

- Manual latch and dead-bolt
- SUPPLIED AS STANDARD:
Striking plate item 1.06218.00.0 (L=37 mm.)

2	22	40	1,047	1	1	12015	40	0			
2	22	50	1,100	1	1	12015	50	0			
2	22	60	1,180	1	1	12015	60	0			
2	22	70	1,188	1	1	12015	70	0			

- Automatic latch and dead-bolt
- SUPPLIED AS STANDARD:
Striking plate item 1.06035.00.0 (L=25 mm.)

2	22	40	0,975	1	1	12011	40	0			
2	22	50	1,055	1	1	12011	50	0			
2	22	60	1,144	1	1	12011	60	0			
2	22	70	1,215	1	1	12011	70	0			

- Automatic latch and dead-bolt
- SUPPLIED AS STANDARD:
Striking plate item 1.06218.00.0 (L=37 mm.)

2	22	40	1,047	1	1	12016	40	0			
2	22	50	1,116	1	1	12016	50	0			
2	22	60	1,180	1	1	12016	60	0			
2	22	70	1,255	1	1	12016	70	0			