



**Technical features:**

- Zinc-plated steel faceplate
- Zinc-plated steel case
- Nickel-plated reversible steel latch
- Single throw (15 mm.) nickel-plated deadbolt
- 9 mm. split follower
- Can be combined with the panic exit devices series 59600 and 59711.10/11.0.00.00.FE

**Hand:**

0 = Non-handed

**Cylinder to be ordered separately**




**Supplied as standard:**

- Instruction sheet

# Sicur Panic

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM			
								Type	Dim.	Hand	Fin.




- FOR SINGLE LEAF DOORS
- Dead-locking latch and deadbolt
- A TYPE OPERATION
- Inside:
  - Panic exit device for opening
  - Key for closing with deadbolt
- Outside:
  - Key for activating latch and deadbolt

1	92	24	25	0,610	1	1	43620	25	0		
1	92	24	30	0,655	1	1	43620	30	0		
1	92	24	35	0,800	1	1	43620	35	0		
1	92	24	40	0,730	1	1	43620	40	0		
1	92	24	45	0,780	1	1	43620	45	0		

- B TYPE OPERATION
- Inside:
  - Panic exit device for opening
  - Key for closing with deadbolt and activating or disactivating external handle for latch operation
- Outside:
  - Key for closing with deadbolt and activating or disactivating external handle for latch operation

1	92	24	25	0,610	1	1	43630	25	0		
1	92	24	30	0,655	1	1	43630	30	0		
1	92	24	35	0,690	1	1	43630	35	0		
1	92	24	40	0,730	1	1	43630	40	0		
1	92	24	45	0,780	1	1	43630	45	0		

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
								Type	Dim.	Hand	Fin.



- FOR DOUBLE DOORS
- Panic lock series 43690 to be installed on secondary leaf
- deadbolt and latch
- A TYPE OPERATION
- Inside:
  - Panic exit device for opening
  - Key for closing with deadbolt
- Outside:
  - Key for activating latch and deadbolt

1	92	24	25	0,560	1	1	43650 25 0
1	92	24	30	0,610	1	1	43650 30 0
1	92	24	35	0,725	1	1	43650 35 0
1	92	24	40	0,770	1	1	43650 40 0
1	92	24	45	0,710	1	1	43650 45 0

- B TYPE OPERATION
- Inside:
  - Panic exit device for opening
  - Key for closing with deadbolt and activating or disactivating external handle for latch operation
- Outside:
  - Key for closing with deadbolt and activating or disactivating external handle for latch operation


1	92	24	25	0,640	1	1	43660 25 0
1	92	24	30	0,610	1	1	43660 30 0
1	92	24	35	0,725	1	1	43660 35 0
1	92	24	40	0,760	1	1	43660 40 0
1	92	24	45	0,710	1	1	43660 45 0

- C TYPE OPERATION
- Replacing series 43631
- Inside:
  - Panic exit device for opening
  - Key for closing with deadbolt and activating external handle for latch operation
- Outside:
  - Key for closing with deadbolt and activating external handle for latch operation

1	92	24	25	0,560	1	1	43661 25 0
1	92	24	30	0,610	1	1	43661 30 0
1	92	24	35	0,640	1	1	43661 35 0
1	92	24	40	0,670	1	1	43661 40 0
1	92	24	45	0,710	1	1	43661 45 0

- D TYPE OPERATION
- Replacing series 43632
- Inside:
  - Panic exit device for opening
  - Key for closing with deadbolt
- Outside:
  - Key for closing with deadbolt. The handle, with deadbolt withdrawn, is activated for latch operation

1	92	24	25	0,560	1	1	43662 25 0
1	92	24	30	0,610	1	1	43662 30 0
1	92	24	35	0,715	1	1	43662 35 0
1	92	24	40	0,760	1	1	43662 40 0
1	92	24	45	0,710	1	1	43662 45 0



- FOR SECONDARY LEAF OF A DOUBLE DOOR
- Panic lock series 43650, 43660, 43661, 43662 to be installed on secondary leaf
- OPERATION:
- Inside:panic exit device
- ON REQUEST:
  - extension bolts item 1.07088.03.0
  - Automatic dogging device item 1.07089.50.0
  - Top striker item 1.06141.80.0

28	30	0,795	1	1	43690 30 0
28	40	0,865	1	1	43690 40 0
28	60	1,020	1	1	43690 60 0
28	75	1,100	1	1	43690 75 0