



Technical features:

- Steel sliding arm with or without hold open device
- Cam operated.
- Adjustment valve with thermostatic device.

Operation:

- Adjustable closing speed and end stroke
- Backcheck
- Adjustable strength
- Backcheck (opening brake)

Supplied as standard:

- Screws
- Adhesive templates



Finishes:

- SUPPLIED AS STANDARD:
 - Aluminum (fin. 97)
- FINISH OPTIONS:
 - Black (fin. 44)
 - White (fin. 45)
 - Champagne (fin. 87)
 - Brown (fin. 88)
 - Matt black (fin. 90)

Standards:

- CE marking in compliance with EN 1154 standard

D6200

Type	Description	Closing strength	Max. door width	Max. door weight	Unit weight	Pieces	ITEM				
							Type	Dim. Hand	Fin.	Pers.	Spec.
	<ul style="list-style-type: none"> • For inward opening doors (door closer body installed on the door leaf and arm on the door frame) • Standard track arm 	2÷4	1100	80	2,300	1	1 D6200 03 0 97				
	<ul style="list-style-type: none"> • For outward opening doors (door closer body installed on the door leaf and arm installed on the frame) • Standard track arm 	2÷4	1100	80	2,300	1	1 D6210 03 0 97				
	<ul style="list-style-type: none"> • Hold open unit for D6200 series 	-	-	-	-	1	1 07209 02 0				