



**Technical features:**

- Non-handed handle.
- Idle handle under no power input conditions.
- Key operated mechanical emergency system: the key will operate the handle. By removing the key the handle will be deactivated.
- Wiring system with connector for complete connection insulation.
- LED integral with handle body for door status visual indication.
- Nickel-plated steel case.
- Painted aluminum alloy cover.
- Electric hold-open device available.
- Powered through booster device
- Rated voltage 12/24 V ac/dc.
- Operating voltage min. 5 V, max 28 V.

**Supplied as standard:**

- Cylinder item 1.0G304.02.0.12.
- Booster module item 1.07022.01.0.
- 8/9 mm square spindle.


**On request:**

- Timer item 1.07022.20.0

**Finishes:**

- Black painted (RAL 9005).
- Grey painted (RAL 9006).

| Type | Description | Faceplate | Unit weight<br> | Pieces<br> | ITEM |              |      |                |
|------|-------------|-----------|-----------------|------------|------|--------------|------|----------------|
|      |             |           |                 |            | Type | Dim.<br>Hand | Fin. | Pers.<br>Spec. |



- Electrically enabled handle
- Can be installed with panic exit devices series FAST and Cisa Prestige
- Painted Black
- STD SUPPLY:  
Booster device 1.07022.01.0  
Connecting cable  
fixing screws
- ON REQUEST:  
Timer device 1.07022.20.0

1,200 1 1 07074 80 0