







## Technical features:

- Zinc plated steel faceplate
- Zinc plated steel case
- Zinc plated steel latch
- 9 mm. through follower

## Hand:

0 = Non-handed

Cylinder to be ordered separately



## Mito

Туре

Description








**ITEM** 







- 12 V dc 800 mA
- OPERATION:

Inside: with the handle or the key Outside: with the electrically operated handle and/or the key 72 24 65 0,980

1 13100 65 0



• Latch bolt only

• OPERATION:

Latch withdrawn by key or handle

72 24 65 0,690

24 1 43000 65 0



- Dead-bolt and latch
- 15 mm. throw
- OPERATION: Latch withdrawn by key or handle Dead-bolt withdrawn by key

1 72 24 65 0,746 24 1 43020 65 0




- Dead-bolt and latch
- 15 mm. throw
- Pre-arranged for additional locking points
- OPERATION: Latch withdrawn by key or handle Dead-bolt operated by key
- ON REQUEST: Set of side latches item 1.07090.50.0 Set of rods item 1.07091.50.0

1 72 24 65 0,850 24 1 43024 65 0



Type Description See Fig. 1. The Mark of the Property of the P



• 3 locking points

• OPERATION:

Latch withdrawn by key or handle Dead-bolt operated by key 1 72 24 65 1,750 24 **1 43025 65 0** 



• FOR SECONDARY LEAF OF A DOUBLE DOOR

• OPERATION:

Extended bolts are operated by a front lever located inside the striker

- Rod's forward stroke 17 mm
- ON REQUEST:

Extended bolts item1.07088.03.0 Automatic dogging device item 1.07089.50.0 1 24 0,360 1 **1 43091 00 0**